

Combined LED Emergency Control Gear: EM powerLED PRO DIM C/SR 45W

Highest flexibility with just one unit



EM powerLED PRO DIM C/SR 45 W

- ___ Independent and built-in combined DALI dimmable emergency LED Driver
- ___ General lighting and auto test emergency lighting with just one unit

▼ For general lighting

- ___ 6W to 45W output power
- ___ 20V to 50V forward voltage
- ___ 300mA to 1,400mA selectable with I-SELECT 2 resistor, programmable with DALI or ready2mains
- ___ 1–100% dimmable
- ___ corridorFUNCTION
- ___ Dimensions: built-in 175 x 82 x 34 mm
independent 209 x 82 x 34 mm
- ___ SELV < 60V
- ___ Multi device type (DT1&6): just one DALI address for dimming and emergency
- ___ Must only be used on DALI control systems which can handle multi device types



EM powerLED PRO DIM C 45W



EM powerLED PRO DIM SR 45W

▼ For emergency lighting

- ___ DALI controlled automatic test function
- ___ Power controlled – automatic adjustment of the LED current in emergency mode
- ___ NiCd and NiMH variants for optimal performance
- ___ 1, 2 or 3 hour duration selectable with dip switch

Ordering data

Type	Article number	Rated duration	Number of cells	Packaging, carton	Packaging, pallet
EM powerLED PRO DIM 103 C NiCd 45W 50V	89800433	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 104 C NiCd 45W 50V	89800415	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 103 C NiMH 45W 50V	89800504	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 104 C NiMH 45W 50V	89800508	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 103 SR NiCd 45W 50V	89800434	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 104 SR NiCd 45W 50V	89800416	1/2/3 h	4	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 103 SR NiMH 45W 50V	89800505	1/2/3 h	3	10 pc(s).	400 pc(s).
EM powerLED PRO DIM 104 SR NiMH 45W 50V	89800509	1/2/3 h	4	10 pc(s).	400 pc(s).